



[Zoom](#) | [2](#) | [3](#) | [4](#) | [5](#) | [6](#) | [7](#) |

Machine can pack:

- BD (BluRay) discs
- DVD "Amarey": slim 7.5 mm, slim 9 mm, 15 mm
- DVD "Super Jewel" 10 mm
- CD "Super Jewel" 10 mm
- double CD
- tea
- soap
- perfumes
- cigarettes
- candies
- etc

There is a separate temperature control on both thermo electric heaters, automatic maintenance of temperature in prescribed limits, separate indication of machine's thermo electric heaters heating, possibility to turn off 1 thermo electric heater.

TS-200 has two main distinctions from LM-180, it has a support for packed article that makes a packing process easier, and thermo table, that makes TS-200 an attractive for packing of candies, sets of discs, etc. The thermo table allows performing a thermo shrink.

The quality of the packing depends on operator's skill. As a rule two hours is enough in order operator could start to work on machine pretty confidently. Machine's capabilities and operator's qualification allows to get a high quality of the packed box even without an additional thermo shrink. The DVD containing video film with instruction on operation is applied to the machine.

The machine is dependable and not difficult in operation. Having installed on machine a tear tape [dispenser](#) (which is sold separately) you can pack articles with tear [tape](#). The tear tape is unwound simultaneously with polypropylene film and automatically sticks to it. So, use of this option does not draw operator's attention away from process and does not complicate his operation.

### Engineering data

Productivity	200 packs per hour
Envelope shaping	manual
Cutting-off of the film	automatic

Temperature range	130...170 °C
Temperature stability	± 24 °C
Electric power supply for the thermo electric heater and cutting wire	18...24 Volts
Film type	biaxial oriented polypropylene
Film thickness	20...35 micrometers
Maximal width of roll	235 mm
Maximal roll diameter	370 mm
Internal roll diameter	76 mm
Mode of operation	twenty-four-hour
Type of packing	<a href="#">envelope</a>
Dimension, L * W * H	600 * 290 * 175 mm
Dimension in package	630 * 300 * 220 mm
Weight netto/brutto	10,8 / 11,4 kg
Power consumption	150 Watts
Maximal consumption current	1.53 A